

Bowling: WE ROLL OUT THE NUMBERS

For exact specifications our technical team will be happy to inform you.
NL +31 (0)162 682000 | sales@bowltech.nl
BE +32 (0) 51-490590 | sales@bowltech.be



		Explanation	Fixed/ Variable	Dimensions
A	Installation height	Package thickness from work floor to top of bowling lane	Fixed	40,6 cm
B	Service area	The work area behind the EDGE String pinspotters for maintenance	Variable	1,00 - 1,50 m.*
C	Masking wall	The back wall the bowler faces	Fixed	3,50 m. compared to the back of the pinspotter
D	Pinspotters + lane	Full length of the lane from the foulline	Fixed	20,50 m.
E	Approach	The part where the bowler throws the ball	Variable	3,66 - 5,00 m. (Min. length sportbowling 4,50 m.)
F	Ballreturn size	The machine that the ball returns to after a throw	Fixed	2,46 m.
G	Ballreturn position	Position of this machine on the approach	Variable	1,30 - 2,00 m. from foulline
H	Screens	Screen where the bowler can read his/her score	Variable	1,80 - 2,50 m.
I	Seating	Area where the bowler can sit	Variable	3,66 - x,xx m. (advise is 3,66 m.)
J	Ceiling height	Calculated from under the lanes (the work floor)	Variable	min. 3,40 m. (advise is 4,00 m.)

	Nr of lanes	Lanes/Machines	Approach
1	1	1,909 m.	2,039 m.
2	2	3,458 m.	3,458 m.
3	3	5,328 m.	5,458 m.
4	4	6,845 m.	6,845 m.
6	6	10,233 m.	10,233 m.
8	8	13,621 m.	13,621 m.
10	10	17,009 m.	17,009 m.
12	12	20,396 m.	20,396 m.
14	14	23,784 m.	23,784 m.
16	16	27,172 m.	27,172 m.
18	18	30,559 m.	30,559 m.
20	20	33,947 m.	33,947 m.

* Always check local regulations regarding minimum width, taking into account working conditions, local fire safety regulations or other regulations.
 ** No rights can be derived from these dimensions.