



Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier: Terrain Lane Conditioner

Part Number: 156-8185, 156-8185C, 156-8222, 156-8224

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Bowling lane conditioner

Uses advised against: Uses other than those stated; for industrial/professional use only

1.3 Details of the supplier of the safety data sheet:

Supplier: European Bowling Distribution (EBD)

Address: Brieltjenspolder 42

4921 PJ Made

The Netherlands

Telephone: +31 162 671 084

Email: info@eurbowdis.eu

Manufacturer: Kegel LLC

Address: 1951 Longleaf Blvd

Lake Wales, FL 33859, USA

Email of the competent person responsible for the Safety Data Sheet

SDS@kegel.net

1.4 Emergency Phone: +1 (863) 734-0200 (available from 8 AM – 5 PM EST)

+1 (800) 280-2695 (24 hour; call forwarding service available during non-business hours)

Section 2: Hazards identification

2.1 Classification of the substance or mixture: This mixture is considered hazardous according to (EC) No. 1272/2008 (CLP).

Physical Hazards: Not Classified

Health Hazards: Acute Toxicity (Inhalation) Category 4

Skin Irritant Category 2

Eye Irritant Category 2

Skin Sensitizer Category 1

Environmental Hazards: Aquatic Chronic Category 4

2.2 Label elements



Hazard Pictogram(s): GHS07/Exclamation point

Signal Word: Warning

Hazard statements

H332: Harmful if inhaled

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction

H413: May cause long lasting harmful effects to aquatic life.

Precautionary Statements

Prevention: P261: Avoid breathing dust/fumes/gas/mist/vapors/spray.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

Response: P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/ doctor if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P337+P313: If eye irritation persists get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of water and mild soap.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

Storage:

Disposal: P501: Dispose of contents and container as required by all local, state, federal and international laws or regulations.

2.3 Other hazards: This product does not contain any PBT or vPvB greater than 0,1%.

Section 3: Composition/information on ingredients

3.1 Substances: Not applicable

3.2 Mixture:

Chemical name*	CAS Number	EC Number	Registration Number	Concentration (weight %)	Classification*
White mineral oil (petroleum)	8042-47-5	232-455-8	01-2119487078-27	93	Aspiration Category 1/H304 Aquatic Chronic Category 4/H413
Sunflower oil	8001-21-6	232-273-9	---	4	Not Classified
Tall oil hydroxyethyl imidazoline	Mixture	---	---	2	Acute Toxicity Oral Category 4/H302 Skin Corrosion Category 1B/H314 Eye Damage Category 1/H318 Skin Sensitizer Category 1B/H317 Aquatic Acute Category 1/H400
Polyol ester	Proprietary	---	---	1	Not Classified

*Occupational Exposure Limit(s), if available, are listed in section 8. See section 16 for the full text of the H phrases declared above.

Section 4: First aid measures

4.1 Description of first aid measures

Skin Contact: Wash skin with soap and water. Remove any contaminated clothing and wash clothing before reuse. If irritation persists, seek medical attention.

Eye Contact: Flush eyes thoroughly with water while holding eyes open for at least 15 minutes. If wearing contact lenses, remove lenses and flush eyes for several minutes. If discomfort persists, seek medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical professional. Treat symptomatically. Seek medical attention as necessary. Never give anything by mouth to an unconscious person.

Inhalation: Remove victim to fresh air. Obtain medical attention. Qualified personnel may give oxygen if breathing is difficult or cyanosis (blue discoloration of the skin) is noted. Give artificial respiration if subject is not breathing.

4.2 Most important symptoms and effects, both acute and delayed

Skin Absorption: Harmful effects are not expected from short periods of contact. Prolonged or repeated contact may lead to skin irritation by dermatitis including swelling, redness, drying, itching and cracking.

Eye Contact: Harmful effects are not expected from short periods of contact. Eye irritation including redness and tearing may occur. Corneal inflammation may also occur.

Ingestion: Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury. Ingestion may cause gastrointestinal irritation, nausea and diarrhea. Product ingested in large quantities in concentrated form may cause toxic effects.

Inhalation: This product is not likely to cause an inhalation hazard at normal temperatures and pressures. Inhalation of mist or spray may be harmful and may cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Aspiration may cause pulmonary edema or aspiration pneumonia. Oil deposits in the lung may lead to fibrosis and reduced pulmonary function.

4.3 Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice/attention. Show physician this safety data sheet.

Section 5: Firefighting measures

5.1 Extinguishing Media

Suitable: Treat as an oil fire. Use CO₂, dry powder, universal-type foam, and water fog

Unsuitable: Oil will float on water and can spread any fire.

5.2 Special hazards arising from the substance/mixture: Pressure increases may cause container to burst and material may spatter.

5.3 Advice for firefighters

Special Fire Fighting Procedures: Use water spray to cool fire-exposed containers and structures.

Special Protective Equipment for Firefighters: Wear full protective gear and an approved self-contained breathing apparatus with full face-piece operated in positive pressure mode.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Wear protective clothing including gloves and eye protection when taking up spills. Eliminate any ignition sources. Evacuate untrained personnel.

6.2 Environmental precautions: This product is insoluble in water and will float on the surface. Prevent from entering sewers or drains.

6.3 Methods and material for containment and cleaning up: Floor may be slippery. Use care to avoid falling. Cover drains and use spill dams to prevent material from spreading. Absorb spill on an inert material such as sand, earth, or vermiculite. Universal sorbent pads or oil sorbents may also be used. Small spills can be mopped away with water. Never return spills to original container for re-use. Spill clean-up materials should be collected in appropriately labeled containers for disposal. Dispose of material as required by all applicable regulations and laws.

6.4 Reference to other sections: See section 8 for personal protective equipment and section 13 for disposal considerations.

Section 7: Handling and storage

7.1 Precautions for safe handling: Keep containers tightly closed to prevent contamination. Wear suitable personal protective equipment including gloves and splash resistant eye protection. Wash hands after use.

7.2 Conditions for safe storage, including any incompatibilities: Normal precautions should be followed in handling and storage. Keep away from heat and flame. Keep container tightly closed. Product shelf life is best retained by storage between 20°C and 32°C (68°F - 90°F).

7.3 Specific end use(s): Bowling lane conditioner

Section 8: Exposure controls/personal protection

8.1 Control parameters

Exposure limits/standards

Substance: White Mineral Oil (petroleum) CAS No.: 8042-47-5				
Country	Limit Value (8 hours)	Limit Value (Short term)	Form	Source
Germany	5 mg/m ³	20 mg/m ³ (15 min. avg.)	Respirable fraction	AGS, DFG
Romania	5 mg/m ³	10 mg/m ³ (15 min. avg.)		
Switzerland	5 mg/m ³ (15 min. avg.)		Inhalable fraction	
United States	TWA - 5 mg/m ³	STEL - 10 mg/m ³		OSHA PEL, NIOSH REL

8.2 Exposure controls

8.2.1 Appropriate engineering controls: Mechanical ventilation is suggested but not normally necessary under normal usage of product.

8.2.2 Individual protection measures, such as personal protective equipment

8.2.2.1 Eye and face protection: Appropriate eye protection should always be worn when handling chemicals. Splash resistant eyewear is recommended when splashing is a concern.

8.2.2.2 Skin protection: Wear chemical resistant gloves and protective clothing, such as long sleeves, to minimize skin contact.

8.2.2.3 Respiratory protection: No special respiratory protection is required with normal usage of product.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Water clear liquid with brown color

Odor: Non-objectionable odor

Odor threshold: Not determined

pH: Not determined

Melting/freezing point: Not determined

Initial boiling point: 279°C (534,2°F)

Distillation temperature (90%): 489°C (912,2°F)

Flash Point: 83°C (181°F) by PMCC

Evaporation rate: Not determined

Flammability (solid, gas): Not determined

Explosive limits: Not determined

Vapor pressure: Not determined

Vapor density: Not determined

Relative density (H₂O=1): 0,900 @ 20°C

Solubility in H₂O: Insoluble

Partition coefficient (n-octanol/water): Not determined

Auto Ignition temp.: Not determined

Decomposition temp.: Not determined

Viscosity (cps): 81 @ 20°C

Explosive properties: Not determined

Oxidizing properties: Not determined

Fire point: 204°C (399,2°F) by COC

9.2 Other information

Information not available

Section 10: Stability and reactivity

10.1 Reactivity: Non-reactive when used according to specifications

10.2 Chemical stability: Stable under normal ambient conditions

10.3 Possibility of hazardous reactions: None under conditions of normal use.

10.4 Conditions to avoid: Avoid high heat, flames and sparks as a precaution.

10.5 Incompatible materials Product is normally unreactive.

10.6 Hazardous decomposition products: Burning can produce various oxides and vapors that are potentially dangerous to health.

Section 11: Toxicological information

11.1 Information on toxicological effects: This product has not undergone animal lab testing to determine toxicity. Toxicological data and local effects provided for primary substance(s) in the mixture.

Acute toxicity: Does not meet the criteria for oral or dermal classification. Harmful if inhaled.

Chemical Name (CAS #)	Oral LD50 (method)	Dermal LD50 (method)	Inhalation LC50 (method)
White mineral oil (petroleum) (8042-47-5)	>5000 mg/kg (rat) (OECD 401)	>2000 mg/kg (rabbit) (OECD 402)	>5 mg/L (rat) (OECD 403)

Skin corrosion/irritation: Causes skin irritation.

Chemical Name (CAS #)	Result	Species	Method
Tall oil hydroxyethyl imidazoline (61791-39-7)	Corrosive to skin	Rabbit	OECD 404

Serious eye damage/irritation: Causes serious eye irritation.

Chemical Name (CAS #)	Result	Species	Method
Tall oil hydroxyethyl imidazoline (61791-39-7)	Corrosive to eye	Rabbit	EPA OPP 81-4

Respiratory or skin sensitization: May cause an allergic skin reaction.

Chemical Name (CAS #)	Result	Species	Method
Tall oil hydroxyethyl imidazoline (61791-39-7)	Sensitizing	Guinea pig	OECD 406

Germ cell mutagenicity: Does not meet the criteria for classification.

Carcinogenicity: Does not meet the criteria for classification.

Reproductive toxicity: Does not meet the criteria for classification.

Specific Target Organ Toxicant Single Exposure (STOT-SE): Does not meet the criteria for classification.

Specific Target Organ Toxicant Repeated Exposure (STOT-RE): Does not meet the criteria for classification.

Aspiration hazard: Does not meet the criteria for classification.

Numerical measures of toxicity: The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral): 4539 mg/kg

ATEmix (dermal): 2012 mg/kg

ATEmix (inhalation-vapors): 4,3 mg/L

Section 12: Ecological information

12.1 Toxicity: There is no eco-toxicity data available for this mixture. This product should be kept out of sewage and drainage systems and all bodies of water as the mixture is toxic to aquatic life with long-lasting effects based on the predominant substance(s).

Chemical Name (CAS #)	Vertebrates LC50 (method)	Invertebrates EC50 (method)	Algae EC50 (method)
White mineral oil (petroleum) (8042-47-5)	1000 mg/L (OECD 203)	10000 mg/L (OECD 202)	1000 mg/L (OECD 201)

12.2 Persistence and degradability: Biodegradability has not been determined for the mixture.

Chemical Name (CAS #)	Result	Degradability	Method
White mineral oil (petroleum) (8042-47-5)	Inherently biodegradable	31% in 28 days	OECD 301 F

12.3 Bioaccumulative potential: Data not available for mixture

12.4 Mobility in soil: Data not available for mixture

12.5 Results of PBT and vPvB assessment: Mixture does not contain any PBT or vPvB substances at greater than 0,1%.

12.6 Other adverse effects: Unknown

Section 13: Disposal considerations

13.1 Waste treatment methods: Dispose of all contents/container in accordance with appropriate international, federal, state and local environmental control regulations. Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. The material may be collected and recycled at a licensed and approved chemical collection and disposal facility or at an oil recycling facility. Empty containers should be taken to an approved waste facility for recycling or disposal.

Section 14: Transport information

	ADR/RID (Road/Rail Transport)	IMDG/IMO (Sea Transport)	IATA/ICAO (Air Transport)
14.1 UN number	Not Regulated	Not Regulated	Not Regulated
14.2 UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3 Transport hazard class	Not Regulated	Not Regulated	Not Regulated
14.4 Packing group	None	None	None
14.5 Environmental hazards	None	None	None

14.6 Special precautions for user: Always transport in closed containers that are upright and secure to prevent accidental spillage.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation (EC) No 1907/2006

This mixture contains only components that have been registered, are exempt from registration, or are regarded as registered according to Regulation (EC) No. 1907/2006 (REACH).

Seveso Directive 2012/18/EC – Listed in regulation: None

15.2 Chemical safety assessment: No chemical safety assessment has been carried out for this mixture.

Section 16: Other information

Full text of H-phrases, if any, appearing in section 3:

- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H314: Causes severe skin burns and eye damage.
- H317: May cause allergic skin reaction.
- H318: Causes serious eye damage.
- H400: Very toxic to aquatic life.
- H413: May cause long lasting harmful effects to aquatic life.

HMIS III Rating

Health: 1
 Flammability: 1
 Physical Hazard: 0
 Personal Protective Equipment (PPE): B

NFPA Rating

Health: 1
 Flammability: 2
 Reactivity: 0
 Special Hazards: None


Hazard Rating Legend

- 0: Minimal Hazard
- 1: Slight Hazard
- 2: Moderate Hazard
- 3: Serious Hazard
- 4: Severe Hazard

HMIS III Ratings

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PPE	B

NFPA Ratings



SDS: Terrain Lane Conditioner

Product ID: 156-8185, 156-8185C, 156-8222, 156-8224

SDS Revision Level: 1,0

SDS Revision Date: 7 October 2019

Revision Reason(s): New SDS

Notice to Reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.